

## 15 W Sound projector with Hi-Fi loudspeaker



RL-9 / RL-12



RL-11 / RL-14

Sound projectors offered in two versions, thus granting a homogeneous design for all applications. Equipment includes a multi-position swivel bracket for wall and ceiling mounting, furthermore a rigid mounting set for installation in ceilings allowing a vertically downwards directed sound radiation. Delivery of the pendulum version includes 3 m cable and canopy. These 15 W sound projectors are fitted up with a Hi-Fi chassis providing an excellent music reproduction.

Typ	RL-9	RL-10	RL-11
load rating	15W / 100V	15W / 100V	15W / 100V
Impedance	667 Ω	667 Ω	667 Ω
Transformer matching	15 / 7,5 / 3,75	15 / 7,5 / 3,75	15 / 7,5 / 3,75
Sound pressure level (1W/1m)	91dB	91dB	91dB
max. Sound pressure level (1m)	103dB	103dB	103dB
Frequency range (-10dB)	60-20000 Hz	60-20000 Hz	60-20000 Hz
Transmission angle	130°	130°	130°
Dimensions (mm)	Ø 144x210	Ø 144x210	Ø 144x210
Mounting	Aluminium bracket	rigid bracket	Pendulum
weight	2,8 kg	2,8 kg	2,7 kg
Color	silver RAL9006	silver RAL9006	silver RAL9006
Typ	RL-12	RL-13	RL-14
load rating	15W / 100V	15W / 100V	15W / 100V
Impedance	667 Ω	667 Ω	667 Ω
Transformer matching	15 / 7,5 / 3,75	15 / 7,5 / 3,75	15 / 7,5 / 3,75
Sound pressure level (1W/1m)	91dB	91dB	91dB
max. Sound pressure level (1m)	103dB	103dB	103dB
Frequency range (-10dB)	60-20000 Hz	60-20000 Hz	60-20000 Hz
Transmission angle	130°	130°	130°
Dimensions (mm)	Ø 144x210	Ø 144x210	Ø 144x210
Mounting	Aluminium bracket	rigid bracket	Pendulum
weight	2,8 kg	2,8 kg	2,7 kg
Color	white RAL9010	white RAL9010	white RAL9010