


Baffle loudspeaker



SLH-300-1



Baffle speakers to be fixed in ceilings or by free suspension. Acoustic tissues at front and back part grant protection against dust pollution. Three neoprene pads ensure a secure support. Suspension chains are fixed via three drillings. The 130 mm chassis impresses by a very linear frequency range. The models SLH-300-4 and SLH-300-4-10 are made of fireproof material.

Typ	SLH-300-1	SLH-300-1-10	SLH-300-4	SLH-300-4-10
load rating	6W / 100V	10W / 100V	6W / 100V	10W / 100V
Impedance	1667 Ω	1000 Ω	1667 Ω	1000 Ω
Transformer matching	6 / 3 / 1,5	10 / 5 / 2,5	6 / 3 / 1,5	10 / 5 / 2,5
Sound pressure level (1W/1m)	93dB	93dB	93dB	93dB
max. Sound pressure level (1m)	101dB	103dB	101dB	103dB
Frequency range (-10dB)	70-19000 Hz	70-19000 Hz	70-19000 Hz	70-19000 Hz
Transmission angle	180°	180°	180°	180°
Dimensions (mm)	300x300x66	300x300x66	300x300x66	300x300x66
			feuerfest	feuerfest
weight	1,4 kg	1,6 kg	1,4 kg	1,6 kg
Color	black RAL9005	black RAL9005	natural colors	natural colors
Accessories	KH-3	AHK	AHF	
	Suspension chains 3 x 1m	plastic dust cover black	dust cover fireproof	