

Baffle loudspeaker (98 dB/1W/1m)



SLH-300-3

Baffle speaker to be fixed in ceilings or by free suspension. Acoustic tissues at front and back part grant protection against dust pollution. Three neoprene pads ensure a secure support. Suspension chains are fixed via three drillings. The 200 mm Chassis impresses by its high degree of efficiency. The models SLH-300-6 and SLH-300-6-10 are made of fireproof material.

Typ	SLH-300-3	SLH-300-3-10	SLH-300-6	SLH-300-6-10
load rating	6W / 100V	10W / 100V	6W / 100V	10W / 100V
Impedance	1667 Ω	1000 Ω	1667 Ω	1000 Ω
Transformer matching	6 / 3 / 1,5	10 / 5 / 2,5	6 / 3 / 1,5	10 / 5 / 2,5
Sound pressure level (1W/1m)	98dB	98dB	98dB	98dB
max. Sound pressure level (1m)	106dB	108dB	106dB	108dB
Frequency range (-10dB)	50-18000 Hz	50-18000 Hz	50-18000 Hz	50-18000 Hz
Transmission angle	160°	160°	160°	160°
Dimensions (mm)	300x300x95	300x300x95	300x300x95	300x300x95
			feuerfest	feuerfest
weight	1,7 kg	1,9 kg	1,7 kg	1,9 kg
Color	black RAL9005	black RAL9005	natural colors	natural colors
Accessories	KH-3	AHK	AHF	
	Suspension chains 3 x 1m	plastic dust cover black	dust cover fireproof	